

SQL

comandos

```
SHOW VARIABLES LIKE "%version%";
```

postgreSQL

```
SELECT version();</sql>  
<code sql>SELECT * FROM «pg_user»;
```

```
CREATE USER nombre_usuario WITH password '123456';
```

```
DROP USER nombre_usuario;
```

```
ALTER USER usertochange WITH password 'new_passwd';
```

```
ALTER USER mysuper WITH SUPERUSER;  
ALTER USER mysuper WITH SUPERUSER CREATEDB CREATEROLE INHERIT LOGIN REPLICATION;
```

```
CREATE DATABASE nombre_db WITH OWNER nombre_usuario;
```

```
DROP DATABASE nombre_db;
```

```
ALTER DATABASE database_name OWNER TO new_owner;
```

```
SELECT pg_size_pretty(pg_database_size('dbname'));
```

```
TRUNCATE TABLE TABLE RESTART IDENTITY;
```

```
COPY (SELECT * FROM tablename) TO '/home/tablename.csv' WITH DELIMITER '|';
```

- LIMIT : número de registros a mostrar
- OFFSET : a partir de dónde se empezaran a mostrar los registros

/via: <https://medium.com/erdk2/comandos-consola-postgres-54591bdeec0a>

/via: <http://viviryaprenderweb.com/postgres-comandos-basicos-segunda-lista/>

From:
<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:
<https://miguelangel.torresegea.es/wiki/bbdd:sql:start?rev=1606578310>

Last update: 28/11/2020 07:45

