

Sesión 4

resumen

```
docker ps
docker ps -f name=ep_devops_mysql.1
docker ps -f name=ep_devops_mysql.1 -q
docker exec -ti $(docker ps -f name=ep_devops_mysql.1 -q ) /bin/bash
docker logs $(docker ps -f name=ep_devops_mysql.1 -q )
docker logs -f $(docker ps -f name=ep_devops_mysql.1 -q )
```

/via: <https://pic-devops.pad.floss.cat/p/docker-troubleshooting>

TIG (Telegraf+Influxdb+Grafana)

- crear base de datos en influxdb: `curl -i -XPOST http://localhost:8086/query -data-urlencode «q=CREATE DATABASE telegraf`
- borrar base de datos: `curl -i -XPOST http://localhost:8086/query -data-urlencode «q=DROP DATABASE telegraf`
- retencion_policy a XX días para que purge los días y no se limite a X entradas
- importar dashboards: <https://grafana.com/dashboards>

Grafana

- dashboards:
 - visión cluster
 - visión stack y servicios
 - contenedores
- paneles: exportar JSON
- plugin: Diagram (pinta un servicio y estados según valores de métrica)

edición panel

- los elementos que se meten en 1 row se pueden repetir, en función de las variables
- ```
$host = show tag values with key = "host"
$stack = show tag values with key = "com.docker.stack.namespace"
$service = show tag values with key = "com.docker.swarm.service.name" WHERE
"com.docker.stack.namespace" =~ /^$stack/
$container = show tag values with key = "container_name" WHERE "host" =~
/^$host$/ AND "com.docker.stack.namespace" =~ /^$stack/ AND
"com.docker.swarm.service.name" =~ /^$service/
```

## prometheus

- = Grafana + Alertas (aunque Grafana ahora ya si)
- node exporter : telegraf

- prometheus: base datos + alertas
  - <https://stefanprodan.com/2016/a-monitoring-solution-for-docker-hosts-containers-and-containerized-services/>

## ELK

### swarm-ELK.yml

```
Docker Stack to deploy ELK + Logspout
Based on
Updated by: Kenneth Peiruza, kenneth@floss.cat
Sun Mar 4 13:15:47 CET 2018
#
cluster.name: 'docker-cluster'
bootstrap.memory_lock: 'true'
version: '3.4'

services:
 elasticsearch:
 image: docker.elastic.co/elasticsearch/elasticsearch-oss:6.2.2
 environment:
 ES_JAVA_OPTS: '-Xms768m -Xmx768m'
 networks:
 - elasticsearch
 volumes:
 -
 ${REMOTE_BIND}/${STACK_NAME}/elasticsearch/data:/usr/share/elasticsearch/data
 deploy:
 replicas: 1

 logstash:
 image: docker.elastic.co/logstash/logstash-oss:6.2.2
 volumes:
 -
 ${REMOTE_BIND}/${STACK_NAME}/logstash/config:/usr/share/logstash/pipeline/
 depends_on:
 - elasticsearch
 networks:
 - elasticsearch
 - logstash
 deploy:
 replicas: 1

 logspout:
 image: bekt/logspout-logstash
 environment:
 ROUTE_URI: 'logstash://logstash:5000'
 volumes:
 - /var/run/docker.sock:/var/run/docker.sock
 depends_on:
 - logstash
 networks:
 - logstash
 deploy:
```

```
mode: global
restart_policy:
 condition: on-failure
 delay: 30s

kibana:
 image: docker.elastic.co/kibana/kibana-oss:6.2.2
 ports:
 - 5601:5601
 depends_on:
 - elasticsearch
 networks:
 - elasticsearch
 - proxy
 environment:
 ELASTICSEARCH_URL: 'http://elasticsearch:9200'
 deploy:
 replicas: 1
 labels:
 traefik.port: 5601
 traefik.frontend.rule: "Host:${LOGS_URL}"
 traefik.docker.network: "proxy"

networks:
 default:
 driver: 'overlay'
 logstash:
 driver: 'overlay'
 elasticsearch:
 driver: 'overlay'
 proxy:
 external: true
```

```
input {
 udp {
 port => 5000
 codec => json
 }
}

filter {
 if [docker][image] =~ /logstash/ {
 drop { }
 }
}

output {
 elasticsearch { hosts => ["elasticsearch:9200"] }
}
```

+ info:

- Filtros Logstash: <https://www.elastic.co/guide/en/logstash/current/config-examples.html>
- Filtros grok: <https://logz.io/blog/logstash-grok/>

From:  
<https://miguelangel.torresegea.es/wiki/> - **miguel angel torres egea**

Permanent link:  
<https://miguelangel.torresegea.es/wiki/info:cursos:pue:devops:sesion4?rev=1550320274>

Last update: **16/02/2019 04:31**

