

alias

creación

```
alias name=value
alias name='command'
alias name='command arg1 arg2'
alias name='/path/to/script'
alias name='/path/to/script.pl arg1'
```

desactivación (temporal)

```
## path/to/full/command
/usr/bin/clear
## call alias with a backslash ##
\c
## use /bin/ls command and avoid ls alias ##
command ls
```

eliminación (en la sesión)

```
unalias aliasname
unalias foo
```

permanentes

~/bashrc

```
vi ~/.bashrc
## añadir comandos alias
```

acceso privilegiado

```
# if user is not root, pass all commands via sudo #
if [ $UID -ne 0 ]; then
alias reboot='sudo reboot'
alias update='sudo apt-get upgrade'
fi
```

acceso OS

```
### Get os name via uname ###
_myos="$(uname)" ### add alias as per os using $_myos ###
```

```
case $_myos in
Linux) alias foo='/path/to/linux/bin/foo';;
FreeBSD|OpenBSD) alias foo='/path/to/bsd/bin/foo' ;;
SunOS) alias foo='/path/to/sunos/bin/foo' ;;
*) ;;
esac
```

== ejemplos

From:

<https://miguelangel.torresegea.es/wiki/> - **miguel angel torres egea**

Permanent link:

<https://miguelangel.torresegea.es/wiki/linux:bash:alias?rev=1529513002>

Last update: **20/06/2018 09:43**

