

arrays bash

linux, bash, pendiente, wiki

/via: <http://www.thegeekstuff.com/2010/06/bash-array-tutorial/>

más información de interés (arrays indirection)

<http://wiki.bash-hackers.org/syntax/arrays?rev=1534920675>

declaración y asignación

```
array=(valor0 'valor uno' 'valor dos')
```

```
array[0]='valor0'  
array[1]='valor uno'  
array[2]='valor dos'
```

inicialización durante declaración

```
declare -a array=(valor0 'valor uno' 'valor dos')
```

+ asignaciones

```
array[n]=valor  
array[cadena]=valor  
array=valor # se asigna al índice 0 (en asociativos, a "0")  
array=(valor1 valor2 valor3)  
array=( [0]=valor1 1=valor2 2=valor3 )  
array=( [cadena]=valor1 [cadena2]=valor2 )  
array+=(valor5 valor6) # añade  
array=("${otro_array[@]}")
```

recuperación

Sintaxis	Descripción
<code>\${ARRAY[N]}</code>	recupera el elemento N
<code>\${ARRAY[S]}</code>	recupera el elemento S en arrays asociativos
<code><<\${ARRAY[@]}<<</code>	Recupera todos los elementos Si está entrecomillado, @ devuelve cada elemento, * devuelve un único resultado con todos los elementos.
<code>\${ARRAY[@]}</code>	
<code><<\${ARRAY[*]}<<</code>	
<code>\${ARRAY[*]}</code>	Si no lo está, las dos devuelven lo mismo

Sintaxis	Descripción
« \${ARRAY[@]:N:M} «	De funcionamiento similar a la regla anterior, añade que devuelve desde el elemento N, M elementos
\${ARRAY[@]:N:M}	
« \${ARRAY[*]:N:M} «	
\${ARRAY[*]:N:M}	

original

Syntax	Description
\${ARRAY[N]}	Expands to the value of the index N in the indexed array ARRAY. If N is a negative number, it's treated as the offset from the maximum assigned index (can't be used for assignment) - 1
\${ARRAY[S]}	Expands to the value of the index S in the associative array ARRAY.
« \${ARRAY[@]} « \${ARRAY[@]} « \${ARRAY[*]} « \${ARRAY[*]}	Similar to mass-expanding positional parameters , this expands to all elements. If unquoted, both subscripts * and @ expand to the same result, if quoted, @ expands to all elements individually quoted, * expands to all elements quoted as a whole.
« \${ARRAY[@]:N:M} « \${ARRAY[@]:N:M} « \${ARRAY[*]:N:M} « \${ARRAY[*]:N:M}	Similar to what this syntax does for the characters of a single string when doing substring expansion , this expands to M elements starting with element N. This way you can mass-expand individual indexes. The rules for quoting and the subscripts * and @ are the same as above for the other mass-expansions.

metadata

Syntax	Descripción
\${#ARRAY[N]}	Longitud del elemento N
\${#ARRAY[STRING]}	idem en asociativo
\${#ARRAY[@]} \${#ARRAY[*]}	Número de elementos
\${!ARRAY[@]} \${!ARRAY[*]}	Extrae los índices del array, @ elemento a elemento, * en un bloque (desde BASH 3.0)

original

Syntax	Description
\${#ARRAY[N]}	Expands to the length of an individual array member at index N (stringlength)
\${#ARRAY[STRING]}	Expands to the length of an individual associative array member at index STRING (stringlength)
\${#ARRAY[@]} \${#ARRAY[*]}	Expands to the number of elements in ARRAY
\${!ARRAY[@]} \${!ARRAY[*]}	Expands to the indexes in ARRAY since BASH 3.0

destrucción

The [unset](#) builtin command is used to destroy (unset) arrays or individual elements of arrays.

Syntax	Description
unset -v ARRAY unset -v ARRAY[@] unset -v ARRAY[*]	Destroys a complete array
unset -v ARRAY[N]	Destroys the array element at index N
unset -v ARRAY[STRING]	Destroys the array element of the associative array at index STRING

usar siempre comillas para encerrar la variable para evitar problemas con las variables glob

mostar array/elementos/subcadenas

- todo el array: `echo ${array[@]}`
- un elemento: `echo ${array[n]}`
- del elemento n al m: `echo ${array[@]:n:m}`
- del elemento n, subcadena a-b: `echo ${array[n]:a:b}`

longitud

- del array: `echo ${#array[@]}`
- del primer elemento: `echo ${#array}`
- del tercero: `echo ${#array[2]}`

adición / eliminación / sustitución elementos

- añadir elemento(s) a un array existente: `array=(«${array[@]}» «valor 3» «valor 4»)`
- eliminar un elemento n: `unset array[n]`
 - existe forma de eliminar el índice o eliminar por patrón
- eliminar un array: `unset array`
- cambiar string1 por string2: `${array[@]/string1/string2}`
- copiar un array: `new_array=(«${array[@]}»)`
- concatenar arrays: `new_new_array=(«${array[@]}» «${new_array[@]}»)`

cargar contenido de un fichero

- `array=(` cat file `)`

funky constructs

- todos los items del array: `${array[*]}`
- todos los índices del array: `${!array[*]}`
- número de items: `${#array[*]}`
- vía: <http://www.linuxjournal.com/content/bash-arrays>

ejemplos

quoted "*", quoted "@", unquoted

```
#!/bin/bash

array=("first item" "second item" "third" "item")

echo "Number of items in original array: ${#array[*]}"
```

```
for ix in ${!array[*]}
do
    printf "    %s\n" "${array[$ix]}"
done
echo

arr=(${array[*]})
echo "After unquoted expansion: ${#arr[*]}"
for ix in ${!arr[*]}
do
    printf "    %s\n" "${arr[$ix]}"
done
echo

arr=("${array[*]}")
echo "After * quoted expansion: ${#arr[*]}"
for ix in ${!arr[*]}
do
    printf "    %s\n" "${arr[$ix]}"
done
echo

arr=("${array[@]}")
echo "After @ quoted expansion: ${#arr[@]}"
for ix in ${!arr[*]}
do
    printf "    %s\n" "${arr[$ix]}"
done
```

resultado:

```
Number of items in original array: 4
    first item
    second item
    third
    item

After unquoted expansion: 6
    first
    item
    second
    item
    third
    item

After * quoted expansion: 1
    first item second item third item

After @ quoted expansion: 4
    first item
    second item
    third
    item
```

From:

<https://miguelangel.torresegea.es/wiki/> - **miguel angel torres egea**

Permanent link:

<https://miguelangel.torresegea.es/wiki/linux:bash:arrays?rev=1539083811>

Last update: **09/10/2018 04:16**

