

PS1

simples



```
export PS1="\[\e]0;\u@\h
\w\a\]\[\e[00;33m\]\u\[\e[0m\]\[\e[00;37m\]@\[\e[0m\]\[\e[00;33m\]\h\[\e[0m\]\[\e[0
0;37m\]:\[\e[0m\]\[\e[00;34m\]\w\[\e[0m\]\[\e[00;37m\]\n\$ \[\e[0m\]"
```



```
export PS1="\$(tput sgr0)\]\033[38;5;15m\033[38;5;11m\u\$(tput
sgr0)\]\033[38;5;15m\033[38;5;15m@\$(tput
sgr0)\]\033[38;5;15m\033[38;5;11m\h\$(tput
sgr0)\]\033[38;5;15m\033[38;5;15m:\$(tput
sgr0)\]\033[38;5;15m\033[38;5;2m\w\$(tput
sgr0)\]\033[38;5;15m\033[38;5;15m\n\$(tput sgr0)\]\$ \$(tput sgr0)\ \$(tput
sgr0)\]"
```

soporte GIT

ejemplos y fuentes de ideas

`__git_ps1()`

```
export PS1="\n\[\033[1;30m\][\$: \$PPID - \j:\! \[\033[1;30m\]]\[\033[0;36m\] \T
\
\[\033[1;30m\]\[\033[1;34m\]\u@H\[\033[1;30m\]:\[\033[0;37m\]\${SSH_TTY:-o} \
\[\033[0;32m\]+\${SHLVL}\[\033[1;30m\]]
\[\033[1;37m\]\w\[\033[0;37m\]\[\033[1;34m\]\$(__git_ps1 \" (%s)\")
\[\033[0;37m\] \n\$ "
```

gestión de colores

```
set_prompt()
{
    local last_cmd=$?
    local txtreset='$(tput sgr0)'
    local txtbold='$(tput bold)'
    local txtblack='$(tput setaf 0)'
    local txtred='$(tput setaf 1)'
    local txtgreen='$(tput setaf 2)'
    local txtyellow='$(tput setaf 3)'
    local txtblue='$(tput setaf 4)'
    local txtpurple='$(tput setaf 5)'
    local txtcyan='$(tput setaf 6)'
    local txtwhite='$(tput setaf 7)'
    # unicode "□"
```

```

local fancyx='\342\234\227'
# unicode "☐"
local checkmark='\342\234\223'
# Line 1: Full date + full time (24h)
# Line 2: current path
PS1="\[$txtbold\]\[$txtwhite\]\n\D{%A %d %B %Y
%H:%M:%S}\n\[$txtgreen\]\w\n"
# User color: red for root, yellow for others
if [[ $EUID == 0 ]]; then
    PS1+="\[$txtred\]"
else
    PS1+="\[$txtyellow\]"
fi
# Line 3: user@host
PS1+="\u\[$txtwhite\]@\h\n"
# Line 4: a red "☐" or a green "☐" and the error number
if [[ $last_cmd == 0 ]]; then
    PS1+="\[$txtgreen\]$checkmark \[$txtwhite\](0)"
else
    PS1+="\[$txtred\]$fancyx \[$txtwhite\]($last_cmd)"
fi
# Line 4: green git branch
PS1+="\[$txtgreen\](__git_ps1 '(%s)')\[$txtwhite\]"
# Line 4: good old prompt, $ for user, # for root
PS1+=" \\\$ "
}
PROMPT_COMMAND='set_prompt'

```

From:

<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:

<https://miguelangel.torresegea.es/wiki/linux: bash: ps1?rev=1531034377>Last update: **08/07/2018 00:19**