

rsync.sh

```
#!/bin/bash
#
# parametros RSYNC
# - r == recursive
# - p == preserve permissions
# - t == preserve times
# - q == supress non-error messages
# - o == preserve owner
# - g == preserve group
# - L == copy-links
# - v == verbose

RSYNC=/usr/bin/rsync
SSH=/usr/bin/ssh
KEY=/root/.ssh/rsa_192.168.3.199
RUSER=backup
RHOST=192.168.3.199
RPATH=/home/backup
LPATH=/home/backups/wardog.eurorscg.es
TITLE="to_be_changed"
DATE=`eval date +%y%m%d`

# $RSYNC -az -e "$SSH -i $KEY" $RUSER@$RHOST:$RPATH $LPATH
$RSYNC -rL -ptog -q --log-file="$DATE-$TITLE.tmp" -e "$SSH -i $KEY"
$RUSER@$RHOST:$RPATH $LPATH > /dev/null
mail -s "RSYNC $TITLE finished" mate@eurorscg.es < $DATE-$TITLE.tmp 2>/dev/null
rm $DATE-$TITLE.tmp
```

From:

<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:

<https://miguelangel.torresegea.es/wiki/linux:scripts:rsync?rev=1317200271>

Last update: **15/11/2011 01:59**

