

NFS

información

- <http://es.tldp.org/Manuales-LuCAS/GARL2/garl2/x-087-2-nfs.html>
- mount -t nfs nfs_volume local_dir options (se puede omitir -t nfs pq el formato de montaje es exclusivo de este protocolo)
 - mount -t nfs vlayer:/home /users
- cat /proc/filesystems → ha de aparecer «nfs»

puesta en marcha de server/client

- server :
 - configuración servicio:

```
sudo apt-get install nfs-kernel-server nfs-common portmap
sudo vim /etc/exports # añadir el recurso, con parámetros y restricciones
(según más abajo)
sudo exportfs -ra
sudo service nfs-kernel-server start
# alternativamente: sudo systemctl restart nfs-kernel-server
showmount -e
```

- configuración directorio compartido:

```
mkdir /path/directorio/compartido
chown nobody:nogroup /path/directorio/compartido
```

- client :

```
sudo apt-get install nfs-common
sudo /etc/hosts # añadir, opcionalmente, la IP de la máquina remota y su
"alias"
sudo mount -t nfs <ip>:<ruta> <ruta_local>
```

/etc/fstab

```
<ip_NFS_server>:/path/directorio/compartido /punto/montaje nfs
rw,async,hard,intr,noexec 0 0
```

- flags:
 - rw: Read/write filesystem.
 - ro: Read-only filesystem. Remote NFS clients can't modify the filesystem.
 - hard: Applications using files stored on an NFS will always wait if the server goes down. User cannot terminate the process unless the option intr is set.
 - soft: Applications using files stored on an NFS will wait a specified time (using the timeo option) if the server goes down, and after that, will throw an error.
 - intr: Allows user interruption of processes waiting on a NFS request.
 - timeo=<num>: For use with the soft option. Specify the timeout for an NFS request.
 - nolock: Disable file locks. Useful with older NFS servers.
 - noexec: Disable execution of binaries or scripts on an NFS share.

- nosuid: Prevents users from gaining ownership of files on the NFS share.
- rsize=<num>: Sets the read block data size. Defaults to 8192 on NFSv2 and NFSv3, and 32768 on NFSv4.
- wsize=<num>: Sets the write block data size. Defaults to 8192 on NFSv2 and NFSv3, and 32768 on NFSv4.

/etc(exports

[/etc\(exports](#)

```
/path/directorio/compartir [<ip> | <rango_ip>]/<mascara>(flags)
```

- flags:
 - rw : lectura-escritura
 - ro : solo lectura
 - root_squash : impide que un cliente remoto con permiso ROOT pueda ejercerlos
 - subtree_check : Disable file location checks on partial volume exports. This option will speed up transfers on full volume exports.
 - sync : Force all transfers to operate in synchronous mode, so all clients will wait until their operations are really done. This can avoid data corruption in the event of a server crash.

apuntes

- quien puede montar ([/etc\(exports](#)) :

[/etc\(exports/](#)

```
/carpeta ip/mask (ro,root_squad) @ trusted (rw,no_root_squad)
```

- AUTOFS daemon
 - /etc/auto.master

+ info

- <https://www.linode.com/docs/networking/nfs/how-to-mount-nfs-shares-on-debian-9/>

From:

<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:

<https://miguelangel.torresegea.es/wiki/linux:tcpip:nfs?rev=1550965400>

Last update: **23/02/2019 15:43**

