

telegram

create bot

telegram commands

- @BotFather
 - /newbot
 - → API TOKEN
 - /setuserpic
- @userinfobot : nos da nuestro ID usuario telegram

info

- <https://www.shellhacks.com/telegram-api-send-message-personal-notification-bot/>
- <https://ugeek.github.io/blog/post/2019-03-14-crea-un-bot-de-telegram-con-bash-y-una-sola-linea-de-terminal.html>

shell script

telegram-test.sh

```
#!/bin/bash
function sendTelegram {

local TEXT=$1
local SERVER="K0"
#local MESSAGE=$2

#[[ ! -z "$MESSAGE" ]] && \
    curl -s -X POST $URL -d chat_id=$CHAT_ID -d text="*${SERVER}*: $TEXT" -d
    parse_mode="markdown" >> /tmp/telegram.log

}

TOKEN=<YOUR_TOKEN_HERE>
CHAT_ID=<YOUR_CHAT_ID_HERE>
MESSAGE="Hello World"
URL="https://api.telegram.org/bot$TOKEN/sendMessage"

sendTelegram "testing _markdown_
[enlace](https://miguelangel.torresegea.es/wiki)"
```

ovh-test

```
#!/bin/bash

function sendTelegram {
    local ID=$1
```

```

local MESSAGE=$2

[[ ! -z "$MESSAGE" ]] && curl -s -X POST $URL -d chat_id=$CHAT_ID -d
text="$ID disponible" >> /tmp/ovh.log
}

TOKEN=<YOUR_TOKEN_HERE>
CHAT_ID=<YOUR_CHAT_ID_HERE>
MESSAGE="Hello World"
URL="https://api.telegram.org/bot$TOKEN/sendMessage"
JQ_PATH="/usr/local/bin/"

wget -O /dev/shm/ovh.json
https://ca.ovh.com/engine/api/dedicated/server/availabilities\?country=es >
/dev/null

jsonfiltrado=$((${JQ_PATH}jq '.[ ] | select(.hardware == "1801sk13") |
select(.region == "europe") | .datacenters | .[ ] | select(.availability !=
"unavailable")' /dev/shm/ovh.json)
sendTelegram "1801sk13" $jsonfiltrado

#curl -s -X POST $URL -d chat_id=$CHAT_ID -d text="$MESSAGE"

```

1. !/bin/bash

```
function sendTelegram {
```

```
local TEXT=$1 local SERVER=«K0»
```

1. local MESSAGE=\$2

1. ! -z "\$MESSAGE" && \

```
curl -s -X POST $URL -d chat_id=$CHAT_ID -d text=«*${SERVER}*: $TEXT» -d parse_mode=«markdown» »
/tmp/telegram.log
```

```
}
```

```
TOKEN=<YOUR_TOKEN_HERE> CHAT_ID=<YOUR_CHAT_ID_HERE> MESSAGE=«Hello World» UR
L=«https://api.telegram.org/bot$TOKEN/sendMessage»
```

1. whois mate.cat | grep Date > ./mate.cat.tmp

```
whois mate.cat > ./mate.cat.tmp
```

```
-f ./mate.cat.txt && {
```

```

DIFF=$(diff ./mate.cat.txt ./mate.cat.tmp)
[[ $? != 0 ]] && {
    mv ./mate.cat.tmp ./mate.cat.txt
    sendTelegram "cambios en mate.cat: \`${DIFF}\`"
} || {
    rm ./mate.cat.tmp
}

```

```
} || {
```

```
whois mate.cat > ./mate.cat.txt
```

```
}
```

whois

From:

<https://miguelangel.torresegea.es/wiki/> - **miguel angel torres egea**

Permanent link:

<https://miguelangel.torresegea.es/wiki/software:telegram:start?rev=1580598144>

Last update: **01/02/2020 15:02**

