

docker-compose casos de uso

docker-compose

mariadb + adminer

```
version: '3.9'

services:
  db:
    image: mariadb
    ports:
      - "3306:3306"
    volumes:
      - ./data/db:/var/lib/mysql
    env_file:
      - db.env
    container_name: mariadb

  adminer:
    image: adminer
    restart: unless-stopped
    ports:
      - 8080:8080
```

sftp

- mapea en la carpeta home del usuario especificado (no se puede sustituir el \$HOME)
- permite mapear varios usuarios
- permite encriptación de contraseñas
- permite certificados

[docker-compose.yml](#)

```
sftp:
  image: atmoz/sftp
  volumes:
    - ${PWD}/upload:/home/foo/upload
  ports:
    - "2222:22"
  command: foo:user123:1001
```

portainer

[docker-compose.yml](#)

```
version: '2'

services:
  portainer:
    image: portainer/portainer
    restart: always
    container_name: "portainer-app"
#   command: --templates http://templates/templates.json
    ports:
      - "9000:9000"
    networks:
      - local
    volumes:
      - /var/run/docker.sock:/var/run/docker.sock
      - ./data:/data

networks:
  local:
    driver: bridge
```

mysql

docker-compose.yml

```
version: '3.6'

services:
  db:
    image: mysql:5.7
    volumes:
      - db_data:/var/lib/mysql
    environment:
      MYSQL_ROOT_PASSWORD: ${MYSQL_ROOT_PASSWORD}
      MYSQL_DATABASE: ${MYSQL_DATABASE}
      MYSQL_USER: ${MYSQL_USER}
      MYSQL_PASSWORD: ${MYSQL_PASSWORD}
    networks:
      mi-network:
        ipv4_address: 172.22.0.10
    ports:
      - 3306:3306

volumes:
  db_data:
    driver: local
    driver_opts:
      type: 'none'
      o: 'bind'
      device: '${MYSQL_STORAGE_PATH}'

networks:
```

```
# docker network create --attachable --subnet 172.22.0.0/24 mi-network
mi-network:
  external: true
```

PHP + MARIADB (FIDMAG)

start

```
docker-compose -d up
```

files

Dockerfile

```
FROM php:7.2-apache

ENV APACHE_DOCUMENT_ROOT /var/www/intranet/www

RUN apt-get update -y \
  && apt-get install -y libpng-dev libwebp-dev libjpeg62-turbo-dev libxpm-
dev \
  && docker-php-ext-install mysqli \
  && a2enmod rewrite \
  && rm -rf /var/lib/apt/lists/*

RUN docker-php-ext-configure gd \
  --with-gd \
  --with-webp-dir \
  --with-jpeg-dir \
  --with-png-dir \
  --with-xpm-dir \
  && docker-php-ext-install gd

RUN sed -ri -e 's!/var/www/html!${APACHE_DOCUMENT_ROOT}!g' /etc/apache2/sites-
available/*.conf

RUN sed -ri -e 's!/var/www/!${APACHE_DOCUMENT_ROOT}!g'
/etc/apache2/apache2.conf /etc/apache2/conf-available/*.conf

CMD /usr/sbin/apache2ctl -D FOREGROUND
```

docker-compose.yml

```
version: '3.7'

services:
  app:
    build: .
    image: fidmag:7.2-php-apache
    ports:
```

```
- "80:80"
volumes:
  - /home/mtorrese/GIT/intranet_fidmag_org:/var/www/intranet
depends_on:
  - "db"
container_name: php

db:
  image: mariadb
# restart: always
ports:
  - "3306:3306"
volumes:
  - ./data/db:/var/lib/mysql
env_file:
  - db.env
container_name: db
```

```
MYSQL_ROOT_PASSWORD=toor
MYSQL_DATABASE=intranet-docker
MYSQL_USER=intranet-docker
MYSQL_PASSWORD=intranet-docker
```

From: <https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link: <https://miguelangel.torresegea.es/wiki/tech:docker:docker-compose:casosuso?rev=1729352781>

Last update: 19/10/2024 08:46

