

docker run

usos útiles

ftpserversh

```
# https://github.com/stilliard/docker-pure-ftpd
docker run \
  -v ${PWD}/data:/home/bob/files \
  -e FTP_PASSIVE_PORTS=10000:10009 \
  -p 10000-10009:10000-10009 \
  -expose=10000-10009 \
  -p 21:21 \
  -e FTP_USER_NAME=bob \
  -e FTP_USER_PASS=12345 \
  -e FTP_USER_HOME=/home/bob \
  stilliard/pure-ftpd
```

mysqldump.sh

```
# https://hub.docker.com/r/schnitzler/mysqldump
# now=$(date +"%s_%Y-%m-%d")
docker run \
  --rm \
  --entrypoint "" \
  -v $PWD/backup:/backup \
  -e MYSQL_HOST=<HOST> \
  -e MYSQL_PORT=<PORT> \
  -e MYSQL_USER=<USER> \
  -e MYSQL_PASSWORD=<PASSWORD> \
  -e MYSQL_DATABASE=<DB> \
  schnitzler/mysqldump \
  mysqldump --opt -h <HOST> -P<PORT> -u <USER> -p"<PASSWORD>" "--result-
file=/backup/$(date +"%Y-%m-%d-%s")_${MYSQL_DATABASE}.sql" <DB>
```

From:

<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:

<https://miguelangel.torresegea.es/wiki/tech:docker:run?rev=1565688227>

Last update: **13/08/2019 02:23**

