

.git*

git

.gitconfig

- ~/.gitconfig:

```
[alias]
  ck = checkout
  s = status
  l = log --oneline --max-count=10
  ll = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
  lg = log --oneline --decorate --graph
  ls = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
alias = ! git config --get-regexp ^alias\\. | sed -e s/^alias\\.\\.// -e s/\\
/\\ =\\ /
  a = add
  b = branch
  c = commit
  bv = branch -avv
  lv = log --walk-reflogs --max-count=10
  ai = add --interactive
  ss = status --short
```

<https://gist.github.com/johnpolacek/69604a1f6861129ef088>

```
[alias]
  co = checkout
  cob = checkout -b
  coo = !git fetch && git checkout
  br = branch
  brd = branch -d
  brD = branch -D
  merged = branch --merged
  st = status
  aa = add -A .
  cm = commit -m
  aacm = !git add -A . && git commit -m
  cp = cherry-pick
  amend = commit --amend -m
  dev = !git checkout dev && git pull origin dev
  staging = !git checkout staging && git pull origin staging
  master = !git checkout master && git pull origin
  po = push origin
  pod = push origin dev
  pos = push origin staging
  pom = push origin master
  poh = push origin HEAD
  pogm = !git push origin gh-pages && git checkout master && git pull origin
master && git rebase gh-pages && git push origin master && git checkout gh-pages
  pomg = !git push origin master && git checkout gh-pages && git pull origin gh-
pages && git rebase master && git push origin gh-pages && git checkout master
```

```

plo = pull origin
plod = pull origin dev
plos = pull origin staging
plom = pull origin master
ploh = pull origin HEAD
unstage = reset --soft HEAD^
ls = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
ll = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
f = "!git ls-files | grep -i"
gr = grep -Ii
la = "!git config -l | grep alias | cut -c 7-"

```

.gitignore

```

outgoing/*
!outgoing/.gitkeep

data/*
!data/.gitkeep

code/*
!code/fingscan_linux
!code/start.sh
!code/IBScanUltimate_x64_3.9.3.tgz

__pycache__/*

credentials.csv

```

comprobar porqué se ve afectado un fichero:

```
git check-ignore -v <ruta/al/archivo>
```

aunque no esté afectada por ninguna regla:

```
git check-ignore -v --no-index --non-matching <ruta/al/fichero>
```

Eliminar archivos que se estaban rastreando y que se han añadido posteriormente a .gitignore: [git](#), [sacar archivos del índice git \(.gitignore\)](#)

.gitkeep

Fichero vacío para indicar que ese directorio se ha de mantener, aunque no contenga más archivos.

.gitattributes

- [.git* - .gitattributes](#)

From:
<https://miguelangel.torresegea.es/wiki/> - **miguel angel torres egea**

Permanent link:
<https://miguelangel.torresegea.es/wiki/tech:dotfiles>

Last update: **04/05/2026 07:02**

