

vagrant: casos de uso

- [glusterfs vagrant POC](#) [vagrant, vagrantfile](#)
- [3 nodos vagrant + docker](#) [vagrantfile](#)
- [Vagrantfile: multi-machine cluster in a loop](#) [vagrantfile](#)
- [vagrant + docker](#) [vagrantfile](#)
- [master template](#) [vagrantfile](#)
- [vagrant mysql](#) [vagrantfile](#)
- [vagrant php](#) [vagrantfile](#)
- [vagrant tomcat \(7/8\) con JDK \(7/8\)](#) [vagrantfile](#)
- [vagrant + docker + nginx](#) [vagrantfile](#)
- [vagrant weblogic](#) [vagrantfile](#)
 - [tomcat](#)
 - [php](#)
 - [mysql](#)
 - [weblogic](#)
 - [3maquinas](#)
 - [vagrant+docker](#)
 - [master_template](#)
 - [rnxnet](#)

vagrant box

- crear una box en Vagrant:
 1. `vagrant package <nombre_maquina> -output fichero.box`
 2. subir (versión, proveedor, etc...)
 3. descargar (desde otro Vagrantfile):

[Vagrantfile](#)

ejemplos

multi-machine cluster in a loop

```
# -*- mode: ruby -*-
# vi: set ft=ruby :

VAGRANTFILE_API_VERSION = "2"

cluster = {
  "master" => { :ip => "192.168.33.10", :cpus => 1, :mem => 1024 },
  "slave" => { :ip => "192.168.33.11", :cpus => 1, :mem => 1024 }
}
```

```
Vagrant.configure(VAGRANTFILE_API_VERSION) do |config|

  cluster.each_with_index do |(hostname, info), index|

    config.vm.define hostname do |cfg|
      cfg.vm.provider :virtualbox do |vb, override|
        config.vm.box = "ubuntu/trusty64"
        override.vm.network :private_network, ip: "#{info[:ip]}"
        override.vm.hostname = hostname
        vb.name = hostname
        vb.customize ["modifyvm", :id, "--memory", info[:mem], "--cpus",
info[:cpus], "--hwvirtex", "on"]
          end # end provider
        end # end config
      end # end cluster
    end
  end
end
```

/via: <https://gist.github.com/roblayton/c629683ca74658412487>

configuraciones simples

```
Vagrant.configure(2) do |config|
  config.vm.box = "debian/jessie64"
  config.vm.hostname = "pruebal"
  config.vm.provision "shell", path: "actualizar.sh"

  config.vm.network :private_network, ip: "192.168.100.10" # only host
  config.vm.network :public_network, ip: "192.168.100.20"
  config.vm.network :public_network, :bridge=>"eth0"
  config.vm.network :forwarded_port, guest: 80, host: 8080
  config.vm.synced_folder "./www", "/www"

  config.vm.provider "virtualbox" do |vb|
    vb.name = "VM-Pruebal"
    vb.memory = 1024
    vb.cpus = 3
    vb.linked_clone = true
    vb.gui = true
  end
end
```

```
Vagrant.configure("2") do |config|
  config.vm.define "web" do |nodo1|
    nodo1.vm.box = "debian/jessie64"
    nodo1.vm.hostname = "web"
    nodo1.vm.network "public_network", bridge: "eth0"
    nodo1.vm.network "private_network", ip: "10.0.100.101"
  end
  config.vm.define "db" do |nodo2|
```

```
nodo2.vm.box = "debian/jessie64"  
nodo2.vm.hostname = "db"  
nodo2.vm.network "private_network", ip: "10.0.100.102"  
end  
end
```

From:

<https://miguelangel.torresegea.es/wiki/> - miguel angel torres egea

Permanent link:

<https://miguelangel.torresegea.es/wiki/tech:vagrant:casosuso?rev=1637059803>

Last update: **16/11/2021 02:50**

